



Item#: 55119 **LED 2X4 SPEC-SELECT™ CENTER BASKET TROFFER**

2X2 LUMINARIES FOR AMBIENT LIGHTING OF INTERIOR COMMERCIAL SPACES

FEATURES

Spec-Select™ Center Basket Troffers are like 9 fixtures in 1, featuring adjustable wattage and color temperature for the perfect balance of light in any application.

- Adjustable Wattage (3 settings)
- · Adjustable Color (3 settings)
- Integrated Sensor Option (ISO). Sensor sold separately.
- · Designed for T-grid ceilings.

APPLICATION

Offices, hospitals, retail stores, schools lobbies and commercial buildings and work areas.

ELECTRICAL

Wattage	34W / 42W / 50W	
Voltage	120-277V	
Current	50W @ 120V = 0.42A	
Power Factor	0.9	
Total Harmonic Distortion (THD)	10.4	

LIGHTING PERFORMANCE

Lumens	4250 / 5250 / 6250		
Lumens Per Watt (LPW)	125		
Color Temperature (CCT)	3500K / 4100K / 5000K		
Color Rendering (CRI)	82		
R9 (Red Value)	5		
Beam Angle	100°		
Light Distribution	Type VS		
BUG Rating (Backlight, Uplight, and Glare)			
Dimmable Lighting Control	From optional 12VDC sensor, or customer 0-10V controls.		

ENVIRONMENT

Operating Temperature	-4 ~ 122°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP40	

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Seoul 3528
Driver	SIF50-I1100-SS
Sensor Socket	12VDC AUX.

CONSTRUCTION

Housing	Aluminum
Lens	Acrylic (PMMA)
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS





Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: **55119**LED 2X4 SPEC-SELECT™ CENTER BASKET TROFFER




DIMENSIONS (Inches)

Length	47.8"
Width	23.7"
Height	2.1"
Net Weight (Lbs)	11.5

SUPPORTING DOCUMENTS (Grey = not available at this time.) Product Sheet VIEW

Product Sheet	VIEW
Install Instructions	VIEW
IES Download from Web Item	VIEW
LM79	VIEW
LM80	VIEW



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	2	10811768023760	48.4" x 24.4" x 4.9"	
Item	1	811768023763	N/A	N/A
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
55119	LED 2X4 SPEC-SELECT™ CENTER BASKET TROFFER/34-42-50W/35-50K/DIMM/ISO/120-277V - DLC °	2
ACCESSORIES		
54895	PIR DAYLIGHT HARVESTING MICROWAVE SENSOR FOR ISO TROFFER/10-14DC	200
REPLACEMENT PARTS		
SIE50_I1100_SS	REPLACEMENT LED DRIVER	1

ADDITIONAL INFORMATION:

- Default settings; 34W, 5000K.
- The color temperature and wattage may be adjusted by two slide switches integrated into the driver. For additional information refer to the install instructions.

