



V-LOCK. SEE DWG. NO. 208

SURFACE GRADE

LETTERING REQUIREMENTS

STREET CHARACTERISTICS		TEXT SIZE	
STREET TYPE	SPEED LIMIT	UPPER-CASE	LOWER-CASE
MULTI-LANE	MORE THAN 40 MPH	8-INCH	6-INCH
MULTI-LANE	40 MPH OR LESS	6-INCH	4.5-INCH
2-LANE, LOCAL	25 MPH OR LESS	4-INCH	3-INCH
2-LANE, LOCAL	25 MPH OR MORE	6-INCH	4.5-INCH
OVERHEAD MOUNTED SIGNS		12-INCH	9-INCH
SUPPLEMENTAL LETTERS, 6" SIGNS		3-INCH	-
SUPPLEMENTAL LETTERS, SIGNS OVER 6"		4-INCH	-

TEXT SIZE UPPER-CASE	SIZE OF STREET NAME SIGN
8-INCH	10" X 48"
6-INCH	9" X 42"
4-INCH	6" X 30", 6" X 36" OR 6" X 42"

NOTES:

- EXCEPT AS OTHERWISE INDICATED HERE, SIGNS SHALL CONFORM TO THE REQUIREMENTS OF THE CURRENT VERSION OF THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (MUTCD) AND THE OREGON SUPPLEMENT TO THE MUTCD.
- STREET NAME LETTERS SHALL BE COMPOSED OF A COMBINATION OF LOWER-CASE LETTERS WITH INITIAL UPPER-CASE LETTERS. STREET NAME SIGN LETTERS SHALL BE HIGHWAY 'C' FONT.
- STREET NAME SIGNS SHALL BE EXTRUDED ALUMINUM, DOUBLE-FACED WITH HIGH INTENSITY PRISMATIC OR DIAMOND GRADE WHITE ON GREEN REFLECTIVE SHEETING. PROVIDE EACH POLE WITH A SECOND SIGN FOR A CROSSING STREET.
- SIGN LOCATIONS SHALL BE DESIGNATED AND APPROVED BY THE CITY ENGINEER.
- POSTS SHALL BE INSTALLED AND ADDITIONAL SIGNS (STOP, YIELD, ETC.) SHALL BE MOUNTED PER STANDARD DRAWING NO. 208, TYPICAL SIGN INSTALLATION.
- SUPPLEMENTAL LETTERING SHALL BE LOCATED ON THE UPPER CORNERS OF THE SIGN. LETTERS SHALL BE NO CLOSER THAN 1/4" AND NOT FURTHER THAN 1" FROM TOP AND SIDE EDGES OF SIGN AND NO CLOSURE THAN 1" FROM STREET NAME.

CITY OF ALBANY, OREGON PUBLIC WORKS DEPARTMENT		
TYPICAL STREET NAME SIGN		
NO SCALE	JANUARY 2018	NO. 209