



NOTES:

1. POST-CONSTRUCTION MANHOLE FRAME AND COVER ADJUSTMENT WILL ONLY BE ALLOWED WHEN APPROVED BY THE CITY ENGINEER.
2. FINISH ELEVATION OF MANHOLE FRAME AND COVER ASSEMBLIES SHALL BE WITHIN .01 FT. OF THE ADJACENT STREET FINISH GRADE. IF THE DIFFERENCE IN ELEVATION EXCEEDS .01 FT., THE MANHOLE FRAME AND COVER ASSEMBLY SHALL BE ADJUSTED AS SPECIFIED HEREIN.
3. A 4' X 4' SQUARE OF ASPHALT SHALL BE REMOVED AND THE ENTIRE AREA EXCAVATED TO A DEPTH OF 10" BELOW FINISH GRADE OF THE STREET. CONCRETE SHALL BE PLACED TO A DEPTH OF 8" WITHIN THE ENTIRE CUT OUT AREA. THE CONCRETE SHALL BE COVERED WITH CLASS "C" ASPHALT WITH A MINIMUM DEPTH OF 2 INCHES.
4. MAXIMUM DISTANCE BETWEEN THE TOP OF THE CONE SECTION AND FINAL SURFACE GRADE SHALL NOT EXCEED 15".

CITY OF ALBANY, OREGON PUBLIC WORKS DEPARTMENT		
POST-CONSTRUCTION MANHOLE FRAME AND COVER ADJUSTMENT		
NO SCALE	JANUARY 2015	NO. 409