



NOTES

1. PROVIDE PROTECTION FROM ALL VEHICLE TRAFFIC, EQUIPMENT STAGING, AND FOOT TRAFFIC IN PROPOSED FACILITY AREAS PRIOR TO, DURING, AND AFTER CONSTRUCTION.
2. GROWING MEDIUM SHALL BE PLACED IN EVEN LIFTS NO GREATER THAN 8 INCHES IN DEPTH, AS MEASURED LOOSELY. LIFTS SHALL BE MODERATELY COMPACTED BY USE OF A SAND OR WATER FILLED LAWN ROLLER. MECHANICAL COMPACTION WITH JUMPING JACKS OR SIMILAR EQUIPMENT IS PROHIBITED.
3. GROWING MEDIUM IN EACH FACILITY SHALL BE PLACED AND SHAPED THE SAME DAY AND IMMEDIATELY UPON COMPLETION ITS SURFACE SHALL BE PROTECTED WITH STRAW MATTING OR JUTE MATTING.
4. IMPERMEABLE LINER SHALL BE USED ONLY IF REQUIRED ON PROJECT PLANS.
5. VEGETATION: INSTALL PER PLANTING SCHEDULE.
6. IN UNLINED FACILITIES, BOTTOM OF PERFORATED DRAIN PIPE SHALL BE SET AT 2 1/2" ABOVE EXISTING SUBGRADE. IN LINED FACILITIES, BOTTOM PERFORATED DRAIN PIPE SHALL BE SET AT BASE OF DRAIN ROCK LAYER.

CITY OF ALBANY, OREGON		
PUBLIC WORKS DEPARTMENT		
STREETSIDE PLANTERS		
SECTION VIEW		
NO SCALE	JANUARY 2018	NO. 604B